



## HAAS VF2SS

<b>TRAVELS</b>	<b>S.A.E</b>	<b>METRIC</b>
X Axis	30.0 in	762 mm
Y Axis	16.0 in	406 mm
Z Axis	20.0 in	508 mm
Spindle Nose to Table (~ max)	24.0 in	610 mm
Spindle Nose to Table (~ min)	4.0 in	102 mm

<b>SPINDLE</b>	<b>S.A.E</b>	<b>METRIC</b>
Max Rating	30.0 hp	22.4 kW
Max Speed	12000 rpm	12000 rpm
Max Torque	90.0 ft-lbf @ 2000 rpm	122.0 Nm @ 2000 rpm
Drive System	Inline Direct-Drive	Inline Direct-Drive
Taper	CT or BT 40	CT or BT 40
Bearing Lubrication	Air / Oil Injection	Air / Oil Injection
Cooling Liquid Cooled	Liquid Cooled	

<b>TABLE</b>	<b>S.A.E</b>	<b>METRIC</b>
Length	36.0 in	914 mm
Width	14.0 in	356 mm
T-Slot Width	0.626 in to 0.630 in	15.90 mm to 16.00 mm
T-Slot Center Distance	4.92 in	125 mm
Number of Std T-Slots	3	3
Max Wgt on Table (evenly distributed)	1500 lb	680 kg